



| (1) | GHP | ORDERING CODE | SPECIFICATION | | | |
|-----|---|---------------|--|---------------------------|---------------------------|-----------|
| (2) | Material of elements | 1 | Metal parts - nickel - plated brass; seals-oil resistant rubber (-40...100°C) | | | |
| | | 2 | Metal parts - nickel plated brass; seals - silicone rubber (-40...150°C) | | | |
| | | 3 | Cable gland - nickel - plated brass; other metal parts - stainless steel; seals-oil resistant rubber (-40...100°C) | | | |
| | | 4 | Cable gland - nickel - plated brass; other metal parts - stainless steel; seals - silicone rubber (-40...150°C) | | | |
| (3) | Cable gland thread D ₂ | M2 | M20x1.5 | | | |
| | | P1 | Pg16 | | | |
| (4) | Type of cable gland seal | A | Without notches | | | |
| | | B | With notches | | | |
| | | X | No gland, threaded hole only | | | |
| (5) | Type of process thread D ₁ /d ₁ | | D₁ | d₁ [mm] | l₁ [mm] | d4 |
| | | 1 | M24x1,5 | Ø12 | 14 | - |
| | | 2 | Ø15,5 | Ø12 | - | M4x10 |
| | | 3 | G1/2 | Ø12 | 14 | - |
| (6) | Side screw d4=2xM4 | a | Pan head screw made of steel | | | |
| | | b | Cup-point set screw with hex socket made of steel | | | |
| | | c | Pan head screw made of brass | | | |
| | | e | Pan head screw made of stainless steel | | | |
| | | f | Cup-point set screw with hex socket made of stainless steel | | | |
| | | x | No side screw | | | |
| | Cover closure | NS | Screws without leaden seal holes | | | |
| | | LS | Screws with leaden seal holes | | | |
| (8) | Paint type | P | Polyester (~70 µm) | | | |
| | | E | Epoxy (~70 µm) | | | |
| | | C | Creodur - Rafil (~30 µm) | | | |
| (9) | Paint colour | al | alu natural colour (only Creodur - Rafil) | | | |
| | | yc | RAL 1007 daffodil yellow | | | |
| | | ys | RAL 1003 signal yellow | | | |
| | | bs | RAL 5005 signal blue | | | |
| | | sb | RAL 5015 sky blue | | | |
| | | sg | RAL 7032 pebble grey | | | |
| | | gr | RAL 7035 light grey | | | |
| | | ag | RAL 9002 grey white | | | |
| | | sh | RAL 9006 white aluminium | | | |
| | | gs | RAL 9007 grey aluminium | | | |
| cw | RAL 9010 pure white | | | | | |

Main features:

- material of body and cover - aluminium pressure die-castings
- cable gland washer - zinc-plated press steel
- temperature range:
-40÷100°C - oil-proof rubber
-40÷150°C - silicone rubber
- maximum space for transmitter: Ø44x21mm

Ordering example:

(1) (2) (3) (4) (5) (6) (7) (8) (9)
GHP 1 - M1 A - 1 x - NS - P sh