

# SPRINGING LOADED TERMINAL BLOCKS

|  | SBd-B8S-G5Lr   | SBd-B10S-G4Lr  |
|--|--|--|
|  |  |  |
|  | 33   | 33   |
| Place to install                               | „B” type connection heads with 33mm mounting holes spacing |  |
| Type of installation                           | Springing fixed to the connection head by M4 screws        |  |
| Way of connecting with measuring insert        | By pressing  |  |
| Diameter of measuring insert                   | d = 3; 4.5; 6; 8 [mm]                                      |  |
| Max. number of terminals                       | 8  | 6  |
| Max. diameter of inside wire                   | Ø1.2mm   |  |
| Way of connecting inside wire to the terminals | By soldering   |  |
|  | <b>ORDERING</b>  |  |
| Type   | SBd-B8S-G5Lr-2<br>to SBd-B8S-G5Lr-8                        | SBd-B10S-G4Lr-2<br>to SBd-B10S-G4Lr-6                |
| D [mm]   | 3; 4.5; 6; 8   |  |
| Number of terminals                            | 2 to 8   | 2 to 6   |
| <b>Ordering example</b>                        | <b>Spring loaded terminal block SBØ6-B8S-G5Lr-8</b>        | <b>Spring loaded terminal block SBØ6-B10S-G4Lr-6</b> |