

STANDARD TERMINAL BLOCKS

	M5S-VS5	M5S-VS5 for spring loaded version	M5S-VS3L
Place to install	„M” type connection heads with 19 or 20mm mounting holes spacing		
Type of installation	Directly fixed to the connection head by M2.5 or M3 screws	Directly fixed to the connection head by M2.5 or M3 screws	Directly fixed to the connection head by M2.5 or M3 screws, or springing disk
Material of block	Steatite C220 ac. to IEC 60672-3		
Material of terminals	Nickel - plated brass		
Max. number of terminals	4		
Max. diameter of inside wire	Ø1.5mm	Ø1.5mm	Ø1mm
Way of connection inside wire to the terminals	By screwing	By screwing	By soldering
	ORDERING		
Type	M5S-VS5-2 to M5S-VS5-4	M5S-VS5-2 to M5S-VS5-4	M5S-VS3L-2 to M5S-VS3L-4
Number of terminals	2 to 4		
Ordering example:	Terminal block M5S-VS5-2	Terminal block M5S-VS5-2	Terminal block M5S-VS3L-2
<i>Unit for fixing to the connection head</i>			
NAME	TYPE		
Mounting kit	KMD-19 or KMD-20		
<i>Unit for spring loaded version</i>			
Mounting kit	KMF-1		
Springing disk	MSD1-d d = 1.5 ; 3 ; 4.5 ; 6		
Bush springing disk	MSDB1-d d = 1.5; 3; 4.5; 6		

STANDARD
TERMINAL BLOCKS

08