

	M6S-VS2	M6S-VS4	M6S-VS9
	19 20	19 20	19 20
Place to install	„M” type connection heads with 19 or 20mm mounting holes spacing		
Type of installation	Directly fixed to the connection head by M2.5 or M3 screws or springing disk	Directly fixed to the connection head by M2.5 or M3 screws or springing disk	Directly fixed to the connection head by M2.5 or M3 screws
Material of block	Steatite C 220 ac. to IEC 60672-3		
Material of terminals	Nickel - plated brass		
Max. number of terminals	4		
Max. diameter of inside wire	Ø1mm	Ø1mm	Ø1.35mm
Way of connection inside wire to the terminals	By screwing		
	ORDERING		
Type	M6S-VS2-2 to M6S-VS2-4	M6S-VS4-2 to M6S-VS4-4	M6S-VS9-2 to M6S-VS9-4
Number of terminals	2 to 4		
Ordering example:	Terminal block M6S-VS2-4	Terminal block M6S-VS4-4	Terminal block M6S-VS9-2
<i>Unit for fixing to the connection head</i>			
NAME	TYPE		
Mounting kit	KMD-19 or KMD-20		
<i>Unit for spring loaded version</i>			
Mounting kit	KMF-1		
Springing disk	MSD1-d d = 1.5; 3; 4.5; 6		
Bush springing disk	MSDB1-d d = 1.5; 3; 4.5; 6		