

STANDARD TERMINAL BLOCKS

	B7S-HS5	B8S-G4
	33	36
Place to install	„B” type connection heads with 33mm mounting holes spacing	„B” type connection heads - on springing disk of measuring insert with 36mm mounting holes spacing
Type of installation	Directly fixed to the connection head by M4 screws	Riveted to the springing disk by Ø3mm rivets
Material of block	Steatite C220 ac. to IEC 60672-3	Steatite C 220 ac. to IEC 60672-3
Material of terminals	Nickel - plated brass	Nickel - plated brass
Max. number of terminals	2	8
Max. diameter of inside wire	Ø1,5mm for resistant; Ø3mm for thermocouple	Ø1.2mm
Way of connection inside wire to the terminals	By screwing	By screwing
ORDERING		
Type	B7S-HS5-2	B8S-G4-2 to B8S-G4-8
Number of terminals	2	2 to 8
Ordering example:	Terminal block B7S-HS5-2	Terminal block B8S-G4-8
	<i>Unit for fixing to the connection head</i>	-
NAME	TYPE	
Mounting kit	KBD-1	-
	-	<i>Unit for spring loaded version</i>
Mounting kit	-	KBF-3
Springing disk	-	BSD2-d d = 3; 4.5; 6; 8
Bush springing disk	-	BSDB2-d d = 3; 4.5; 6; 8