

	B14S-HS17	B14S-HS18	B15S-G4
	33	33	34
Place to install	„B” type connection heads with 33mm mounting holes spacing	„B” type connection heads with 33mm mounting holes spacing	„B” type connection heads - on springing disk of measuring insert with 34mm mounting holes spacing
Type of installation	Directly fixed to the connection head by M4 screws	Directly fixed to the connection head by M4 screws	Riveted to the springing disk by Ø3mm rivets
Material of block	Steatite C220 ac. to IEC 60672-3		
Material of terminals	Nickel - plated brass		
Max. number of terminals	6		
Max. diameter of inside wire	Ø1.2mm		
Way of connection inside wire to the terminals	By screwing		
	<b>ORDERING</b>		
Type	B14S-HS17-2 to B14S-HS17-6	B14S-HS18-2 to B14S-HS18-6	B15S-G4-2 to B15S-G4-6
Number of terminals	2 to 6		
<b>Ordering example:</b>	<b>Terminal block B14S-HS17-6</b>	<b>Terminal block B14S-HS18-6</b>	<b>Terminal block B15S-G4-6</b>
	<i>Unit for fixing to the connection head</i>	<i>Unit for fixing to the connection head</i>	-
<b>NAME</b>	<b>TYPE</b>		
Mounting kit	KBD-1	KBD-1	-
	-	-	<i>Unit for spring loaded version</i>
Mounting kit	-	-	KBF-3
Springing disk	-	-	BSD2-d d = 3; 4.5; 6; 8
Bush springing disk	-	-	BSDB2-d d = 3; 4.5; 6; 8